



## Description

It is suitable for various sports venues, theater theaters, auditorium classrooms, banquet halls, outdoor performances, multi-functional halls and various high-end application places.

## Feature

- \* Adopt a 15-inch woofer and a 3-inch compression tweeter.
- \* The cabinet adopts 15mm birch board CNC cutting technology, the internal multi-point reinforcement ribs are fixed to increase the stability of the cabinet, and the surface is treated with spraying water-based paint, which is strong and wear-resistant.
- \* One-piece stamping and forming rigid protective mesh grille, with acoustic high sound-transmitting cotton mesh, to protect the speaker and increase the service life.
- \* The two-way frequency-dividing rear-guiding type and special horn design reduce off-axis sound interference, using high-quality filter components and excellent passive filter technology and phase correction technology, the speaker can provide transparent and bright treble, round and clear alto, and full and flexible bass.
- \* Multiple installation holes are reserved in the cabinet to achieve flexible installation methods. Professional speaker sockets and plugs with good electrical characteristics.

## Specification

Model	KS-15
Type	Full range speaker
Rated power	500W
Peak power	2000W
Nominal impedance	8Ω
Frequency range(-10dB)	45HZ-20KHZ
Sensitivity(±3dB)	100dB (1M/1W )
Maximum SPL (rated/peak)	127dB/133dB
Woofer	15" woofer ×1
Tweeter	3" Compression tweeter×1
Coverage angle (-6dB)	100° ( H ) 80° ( V )
Net weight	29.5kg
Dimension (H×W×D)	700×415×410(mm)