

Description

It is used in various medium and high-end KTV entertainment venues.

Features

- * Adopt a 10-inch woofer and a 1.4-inch compression driven tweeter.
 * The cabinet is made of 15mm medium density fiberboard, and adopts water-based paint treatment, wear-resistant and high-grade.
- * The mesh cover uses powder spraying treatment and adopts cotton attachment process to prevent dust or liquid from entering, so as to protect the speaker and prolong the service lifespan.

 * The broadened frequency response characteristics and excellent vocal processing bring the audience and singers a very comfortable experience.

 * Professional speaker sockets and plugs with good electrical characteristics.

Specification:

| Model KT-M10 Rated power 300W Peak power 1200W Nominal impedance 8Ω Frequency range 60Hz-20KHz Sensitivity 96dB (1M/1W) Maximum SPL (rated/peak) 121dB/127dB Woofer 10" × 1 Tweeter 1.4" × 1 Coverage angle (-6dB) 100°(H) 70°(V) Net weight 15kg Dimension (HxWxD) 533x300x340mm | _ | |
|---|--------------------------|----------------|
| Peak power 1200W Nominal impedance 8Ω Frequency range 60Hz-20KHz Sensitivity 96dB (1M/1W) Maximum SPL (rated/peak) 121dB/127dB Woofer 10" × 1 Tweeter 1.4" × 1 Coverage angle (-6dB) 100°(H) 70°(V) Net weight 15kg | Model | KT-M10 |
| Nominal impedance 8Ω Frequency range 60Hz-20KHz Sensitivity 96dB (1M/1W) Maximum SPL (rated/peak) 121dB/127dB Woofer 10" × 1 Tweeter 1.4" × 1 Coverage angle (-6dB) 100°(H) 70°(V) Net weight 15kg | Rated power | 300W |
| Frequency range 60Hz-20KHz Sensitivity 96dB (1M/1W) Maximum SPL (rated/peak) 121dB/127dB Woofer 10" × 1 Tweeter 1.4" × 1 Coverage angle (-6dB) 100°(H) 70°(V) Net weight 15kg | Peak power | 1200W |
| Sensitivity 96dB (1M/1W) Maximum SPL (rated/peak) 121dB/127dB Woofer 10" × 1 Tweeter 1.4" × 1 Coverage angle (-6dB) 100°(H) 70°(V) Net weight 15kg | Nominal impedance | 8Ω |
| Maximum SPL (rated/peak) 121dB/127dB Woofer 10" × 1 Tweeter 1.4" × 1 Coverage angle (-6dB) 100°(H) 70°(V) Net weight 15kg | Frequency range | 60Hz-20KHz |
| Woofer 10" × 1 Tweeter 1.4" × 1 Coverage angle (-6dB) 100°(H) 70°(V) Net weight 15kg | Sensitivity | 96dB (1M/1W) |
| Tweeter 1.4" × 1 Coverage angle (-6dB) 100°(H) 70°(V) Net weight 15kg | Maximum SPL (rated/peak) | 121dB/127dB |
| Coverage angle (-6dB) 100°(H) 70°(V) Net weight 15kg | Woofer | 10" × 1 |
| Net weight 15kg | Tweeter | 1.4" × 1 |
| | Coverage angle (-6dB) | 100°(H) 70°(V) |
| Dimension (HxWxD) 533x300x340mm | Net weight | 15kg |
| Dimension (may b) | Dimension (H×W×D) | 533×300×340mm |