



Professional Speaker

TS-610P/TS-612P/TS-615P



Description:

It works with the audio processor to form a set of high-end entertainment and conference professional sound system with outstanding vocal performance. It is suitable for various high-end conference rooms and multipurpose halls as the main speaker or auxiliary speaker.

Feature:

- * Adopt a mid-woofer and an annular polyethylene diaphragm compressed tweeter.
- * 15mm birch housing, light weight, wear-resistant spray paint treatment, and dust-proof net cotton inside.
- * The frequency divider in precise design is used to optimize the vocal MF performance.
- * The entire series is equipped with efficient high-power amplifier modules and powerful DSP audio processor. Through different applications of the system, it supports comprehensive parameter settings, including 6 parameter equalization, frequency division, delay, and limit.
- * Multiple screw hoisting holes, a pole socket with a diameter of 35mm, various installation methods.

Specification:

Model	TS-610P	TS-612P	TS-615P
Impedance	8Ω	8Ω	8Ω
Frequency response	55Hz-20KHz	50Hz-20KHz	45Hz-20KHz
Rated power	300W	350W	450W
Peak power	1000W	1400W	1800W
Sensitivity	98dB/W/M	99dB/W/M	100dB/W/M
Max SPL(rated/peak)	123dB/128dB	124dB/130dB	127dB/133dB
Coverage angle	(H)80° (V)60°	(H)80° (V)60°	(H)80° (V)60°
Tweeter	1.4" compressed tweeter ×1	1.7" compressed tweeter ×1	1.73" compressed tweeter ×1
Woofer	10" woofer ×1	12" woofer ×1	15" woofer ×1
Line input sensitivity	0dB	0dB	0dB
Dimension (H×W×D)	510×325×300mm	560×360×380mm	660×435×430mm
Weight	18.5Kg	21.8Kg	28.8Kg
Power supply	AC 220V 50Hz	AC 220V 50Hz	AC 220V 50Hz
Power consumption	240W	280W	360W