



# Linear Array Speaker

## TW-210A



### Feature

- \* Composed of two 10-inch high-efficiency subwoofer units and a 75-core tweeter driver.
- \* The high-quality driver is equipped with a dedicated waveguide horn, so as to achieve accurate and uniform coverage within the effective frequency range.
- \* The housing is formed by engineering plastic mold, which meets the IP66 national standard.
- \* The hoist system consist of stainless steel and aluminum alloy, featuring strong weather resistance.
- \* Using high-strength steel mesh and acoustic sound-permeable sponge to prevent dust and water droplets from damaging the speaker unit.
- \* Designed with professional speaker sockets and plugs, featuring good electrical characteristics.
- \* Applied to various performances, outdoor fixed installations, stadiums, squares, and other high-end cultural tourism application scenarios.

### Specification

Model	TW-210A
Speaker type	Two-way full-range speaker
Rated power	500W
Nominal impedance	8Ω
Frequency range (-10dB)	65HZ-20kHz
Sensitivity (1M/1W)	100dB±3dB
Maximum SPL	130dB
Horizontal coverage angle (-6dB)	100°
Vertical coverage angle (-6dB)	Vary with array size and tilt angle
Subwoofer	10-inch subwoofer×2
Tweeter	3-inch tweeter×1
Net weight	27.2kg
Dimension (H×W×D)	350×671×470mm
Protection class	IP66